

0.00 EUR
incl. 19% VAT, plus [shipping](#)

- Mini-PCIe !
- 5G / LTE !
- Global !
- RG255C-GL !



Quectel RG255C-GL Mini PCIe is a 5G RedCap module adopting standard PCI Express® Mini Card form factor (Mini PCIe). Adopting the 3GPP Rel-17 RedCap technology, the module supports 5G LAN*/ Slicing/ URLLC, etc., with a theoretical peak data rate of 223 Mbps in the downlink and 123 Mbps in the uplink. The module supports LTE Cat 4 and 5G Sub-6 SA modes, and is backward compatible with 3GPP Rel-15 and Rel-16 networks. The module can meet customers' different application demands for medium speed, large capacity, low latency, high reliability, etc.

RG255C-GL Mini PCIe module supports Qualcomm® IZat™ location technology Gen 9VT (GPS, GLONASS, NavIC, BDS and Galileo). The integrated GNSS receiver greatly simplifies product design and provides quicker, more accurate and more dependable positioning capability.

A rich set of Internet protocols, industry-standard interfaces (USB 2.0, PCM, UART, etc.) and abundant functionalities (USB drivers for Windows 8.1/ 10/ 11, Linux and Android) extend the applicability of the module to a wide range of RedCap applications.

- Worldwide 5G/ 4G coverage
- 5G SA mode, 5G LAN*/ URLLC/ Slicing supported
- Multi-constellation GNSS receiver available for applications
- requiring fast and accurate fixes in any environment (optional)
- Feature refinements: DFOTA and VoNR/ VoLTE (optional)

Region	Global	
FORM FACTOR	PCIe / 30.0 x 50.95 x 4.95 /11g weight	
5G BANDS (Global)	5G NR: 3GPP Release 17 RedCap SA operation, Sub-6 GHz 5G NR SA: n1/ 2/ 3/ 5/ 7/ 8/ 12/ 13/ 14/ 18/ 20/ 25/ 26/ 28/ 30/ 38/ 40/ 41/ 48/ 66/ 70/ 71/ 77/ 78/ 79 DL 2x2 MIMO: n1/ 2/ 3/ 5/ 7/ 8/ 12/ 13/ 14/ 18/ 20/ 25/ 26/ 28/ 30/ 38/ 40/ 41/ 48/ 66/ 70/ 71/ 77/ 78/ 79	
LTE	LTE-FDD: B1/ 2/ 3/ 4/ 5/ 7/ 8/ 12/ 13/ 14/ 17/ 18/ 19/ 20/ 25/ 26/ 28/ 30/ 66/ 70/ 71 LTE-TDD: B34/ 38/ 39/ 40/ 41/ 42/ 43/ 48 DL 2 x 2 MIMO: B1/ 2/ 3/ 4/ 5/ 7/ 8/ 12/ 13/ 14/ 17/ 18/ 19/ 20/ 25/ 26/ 28/ 30/ 34/ 38/ 39/ 40/ 41/ 42/ 43/ 48/ 66/ 70/ 71	

Operating temperature	-30°C - 75°C Extended: -40 ~ +85°C
Data transmission (Max.)	5G SA Sub-6: 223 Mbps (DL)/ 123 Mbps (UL) LTE: 195 Mbps (DL)/ 105 Mbps (UL)
Interfaces	(U)SIM: x1 UART: x2 USB: 2.0: x1 PCM: x1 I2C: x1 Antennas: Cellular: x2, GNSS: x1
Enhanced features	Digital Audio and VoNR/VoLTE (optional) DTMF: Dual-tone Multi-frequency DFOTA: Delta Firmware over the Air (U)SIM Card Detection
Electrical features	Supply Voltage Range: 3.0–3.6 V, typ. 3.3 V Power Consumption: TBD
Drivers:	Windows 8.1/10/11; Linux 2.6–6.7; Android 4.x–12.x
Certifications	CE/ RCM / FCC/ IC / RoHS